

SPECIFICATIONS SAMPLE

SPECIES:

- o clear, solid, KD VG fir sash and frames
- o solid mahogany sills

STICKING PROFILE

- o 1/2" Ogee as shown on drawings

FINISH:

- o primed inside and out with ZINSSER 1-2-3 Primer-Sealer

GLAZING:

- o 1/2" clear DSB dual glazing, typical, stop glazed as shown
- o BIG STRETCH acrylic caulking setting bed
 - Circle Air Bar Color Choice: BRONZE WHITE MILL

OPERATING HARDWARE (Double Hung)

- o BSI concealed block and tackle balances, installed

OPERATING HARDWARE (Casement/Awning)

- o TRUTH 4 bar stainless steel friction hinges, installed

WEATHERSTRIP

- o RESOURCE CONSERVATION TECH WS33 silicone bulb, kerf-in, installed
 - Circle Color Choice: BRONZE WHITE
- o SCHLEGEL QWS 320 Q-Ion leaf, kerf-in, installed
 - Circle Color Choice: BRONZE WHITE
- o SCHLEGEL PF 130 Polyflex leaf, kerf-in, installed
 - Color: TAN only

FINISH HARDWARE: (optional, by others UON)

SCREENS: (optional)

- o wood frame to match other window parts (metal screen frame available)
- o charcoal fiberglass screen cloth standard (true bronze cloth optional)

SCREEN HARDWARE for CASEMENT/AWNING WINDOWS:

- o TRUTH MAXIM crank operators
- o TRUTH ENTRYGARD 1618 sash locks
 - Circle Color Choice: 03 BRONZE 32 WHITE(other TRUTH hardware colors may be available)
- o STANLEY solid brass spring bolts, 2 / screen @ top corners

SCREEN HARDWARE for DOUBLE HUNG WINDOWS:

- o (2) stainless steel pins @ top
- o STANLEY solid brass spring bolts, 2 / screen @ bottom corners

DELIVERY (Optional)

INSTALLATION BY OTHERS